

# Highly durable & lightweight, perfect for exterior applications

Our Marine Plywood is manufactured with Okoume veneers throughout and is a stable flat panel ideal for many applications. Manufactured and shipped directly from FSC 100% Certified forests in West Africa.

**Okoume Marine Plywood**

## What are the benefits?



**Ideal for bonding & laminating**



**Excellent durability & attractive faces**



**Perfect for cutting**

## Where can I use?



**Portable buildings**



**Walls & floors**



**Cladding & facades**



The mark of responsible forestry

## Fully certified

- ✔ FSC 100% Certified
- ✔ EN 636:2012
- ✔ BS 1088-1:2003
- ✔ EN 13986 - CE2+ Certified
- ✔ UKCA
- ✔ KOMO
- ✔ CARB P2

Faces	Full piece Okoume veneers 1.1 or 1.3mm before sanding
Grading	B/BB, BB/BB, BB/CC
Inner Layers	Equal thickness plies - 100% Okoume
Glue	Class 3 - Outdoor use / Glue Standard EN 314
Dimensional Tolerance	Standard thickness tolerance +/-0.3 mm: EN 324-1 & EN 324-2
Density	470 - 500 kg/m <sup>3</sup>

Speak with our team

www.globalpp.co.uk | T: 020 3793 4104 | E: sales@globalpp.com  
A: 167 - 169 Great Portland Street, 5th Floor, London, W1W 5PF, UK

## Specifications

Thickness	Plies
2.7mm	3
03mm	3
3.6mm	3
04mm	3
05mm	3
06mm	5
08mm	5
09mm	5
10mm	5
12mm	7
15mm	7
18mm	9
22mm	11
25mm	11
30mm	13
35mm	15
40mm	17

**All thicknesses are available in the following sizes:**

- 2440 x 1220mm
- 2500 x 1220mm
- 2150 x 1220mm
- 2150 x 950mm
- 3100 x 1530mm
- 3100 x 1220mm

and "cut to size" available